



Specification:

Repair, maintenance and servicing of forklifts and other industrial trucks guarantee the availability of your equipment for production, material flow or storage use. The ECO-Jack G-Series compact design with integrated pump makes it independent of external pumps and additional hoses. Its low profile lifting claw also allows it to be used on stackers with low floor clearance. Leading European manufacturers of forklift trucks and other industrial trucks have been relying on the ECO-Jack G series for years, and equip their service teams with it.

Technical data of hydraulic jacks:

#	01 101 30 10	520 bar	500 ml	30 kg
HH	140 mm	10000 kg	8000 kg	NH = 0,9 mm / stroke SH = 2,6 mm / stroke
	3 x 75 mm	30 mm	L x B x H 345 x 257 x 263 mm	

Please always observe the operating instructions, their safety instructions and local conditions!

#	Part No.	Maximum operating pressure in bar	Oil quantity in the tank / cylinder in ml. Standard oil HLP 32 other oils on request	Weight kg	Dimensions in mm L x B x H
	Adjustment positions Distances in mm	Maximum stroke in mm	Maximum lifting load with the lifting head in kg	Maximum lifting load with lifting claw in kg	
	Insertion height in mm		Maximum lifting load with the lifting head in kg	Stroke in mm with SH (fast stroke) and NH (normal stroke)	